







TECHNICAL DATA SHEET - FORGOTTEN WOOD SPECIES

AFRORMOSIA

BQAF103 FADED SMOKE



001 PRODUCT DESCRIPTION

| | | |
|-------------------------------------------------------------------------------------|--------------|-------------------------------------------|
|  | Wood type | Afromosia |
|  | Grading | Prime/Rustic A |
|  | Core/backing | Birch plywood |
|  | Coating | Custom -> multiple reactive stains & oils |
|  | Texture | Smooth |
|  | Bevel | Micro V, 2 side |

002 DIMENSIONS

| | | |
|-------------------------------------------------------------------------------------|-------------------|------------------------------------------|
|  | Thickness/surface | 19/32"- 5/32" (15/4 mm) |
|  | Width | 7 3/32" (180 mm) |
|  | Length | 59 1/16" to 114 11/64" (1500 to 2900 mm) |

003 TECHNICAL PERFORMANCE

| | | |
|-----------------------------------------------------------------------------------|-----------------------------|------------------------------------------------------------------------------------------------------------------------|
|  | Norm | En 14342 |
|  | FSC | CU-COC-874752 |
|  | Formaldehyde emission class | Carb2 compliant |
|  | Flammability class | Dfl-s1 |
|  | Underfloor heating | Yes - Warranty certificate available  |
|  | Floor cooling | Yes - Warranty certificate available  |
|  | Thermal conductivity | 0.17 W/mK |
|  | Moisture content | 7 % (+/- 2%) |
|  | Advisory use | Suitable for: residential, commercial, Hospitality, Retail |

004 ADDITIONAL INFORMATION

| | | |
|-------------------------------------------------------------------------------------|--------------|------------------------|
|  | Installation | Glued down |
|  | Jointing | Tongue and groove |
|  | Sanding | Yes (1 mm per sanding) |



PRIME/RUSTIC A

Knots: unlimited/filled

Cracks: permitted

Sapwood: none

