







TECHNICAL DATA SHEET - FORGOTTEN WOOD SPECIES

DOUGLAS




BQD 305 WARM BARK



001 PRODUCT DESCRIPTION

| | | |
|---|--------------|---|
|  | Wood type | Douglas |
|  | Grading | Natural AB |
|  | Core/backing | Birch plywood |
|  | Coating | Custom -> multiple reactive stains & oils |
|  | Texture | Smooth |
|  | Bevel | Micro V, 2 side |

002 DIMENSIONS

| | | Straight | | | |
|---|-----------------------|---|---|---|---|
|  | Thickness/ surface | 43/64"- 13/64" (17/5 mm) | 43/64"- 13/64" (17/5 mm) | 43/64"- 13/64" (17/5 mm) | 43/64"- 13/64" (17/5 mm) |
|  | Width | 7 7/8" (200 mm) | 9 27/32" (250 mm) | 11 13/6" (300 mm) | 13 25/32" (350 mm) |
|  | Length | 59 1/16" to 114 11/64" (1500 to 2900 mm) | 59 1/16" to 114 11/64" (1500 to 2900 mm) | 59 1/16" to 114 11/64" (1500 to 2900 mm) | 59 1/16" to 114 11/64" (1500 to 2900 mm) |

003 TECHNICAL PERFORMANCE

| | | |
|---|-----------------------------|--|
|  | Norm | En 14342 |
|  | FSC | CU-COC-874752 |
|  | Formaldehyde emission class | Carb2 compliant |
|  | Flammability class | Dfl-s1 |
|  | Underfloor heating | Yes - Warranty certificate available  |
|  | Floor cooling | Yes - Warranty certificate available  |
|  | Thermal conductivity | 0.17 W/mK |
|  | Moisture content | 7 % (+/- 2%) |
|  | Advisory use | Suitable for: residential, commercial, Hospitality, Retail |

004 ADDITIONAL INFORMATION

| | | |
|---|--------------|------------------------|
|  | Installation | Glued down |
|  | Jointing | Tongue and groove |
|  | Sanding | Yes (1 mm per sanding) |



NATURAL AB

Knots: unlimited/filled

Cracks: permitted

Sapwood: none

