







TECHNICAL DATA SHEET - OAK COLLECTION

OAK EIGHT

BQO 802 SOFT CHALK



001 PRODUCT DESCRIPTION

| | | |
|---|--------------|--|
|  | Wood type | European Oak |
|  | Grading | Prime, Natural A, Natural AB, Natural B, Art or Art+ |
|  | Core/backing | Birch plywood |
|  | Coating | Multiple reactive stains |
|  | Texture | Brushed |
|  | Bevel | Micro V, V, U. 2 side |

Straight

| | | | | | |
|---|-----------------------|---|---|---|---|
| ↘ | Thickness/ surface | 25/64" - 1/8" (10/3 mm) | 15/32" - 5/32" (12/4 mm) | 15/32" - 5/32" (12/4 mm) | 35/64" - 1/8" (14/3 mm) |
| | ↕ | Width | 7 23/64" (187 mm) | 5 45/64" (145 mm) | 7 3/32" (180 mm) |
| ↔ | Length | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) |

Straight

| | | | | | |
|---|-----------------------|---|---|---|---|
| ↘ | Thickness/ surface | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) |
| | ↕ | Width | 1 31/32" (50 mm) | 6 19/64" (160 mm) | 7 3/32" (180 mm) |
| ↔ | Length | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) |

Straight

| | | | | | |
|---|-----------------------|---|---|---|---|
| ↘ | Thickness/ surface | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) | 3/4" / 5/32" (19/4 mm) |
| | ↕ | Width | 8 21/32" (220 mm) | 9 29/64" (240 mm) | 10 15/64" (260 mm) |
| ↔ | Length | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) | 59 1/16" - 114 11/64" (1500 - 2900 mm) |

Herringbone

Hungarian point chevron

| | | | | | | |
|---|-----------------------|----------------------------|-----------------------------|-----------------------------|----------------------------|-----------------------------|
| ↘ | Thickness/ surface | 35/64" - 1/8" (14/3 mm) | 19/32" / 5/32" (15/4 mm) | 19/32" / 5/32" (15/4 mm) | 35/64" - 1/8" (14/3 mm) | 19/32" / 5/32" (15/4 mm) |
| | ↕ | Width | 4 23/32" (120 mm) | 3 35/64" (90 mm) | 5 33/64" (140 mm) | 3 35/64" (90 mm) |
| ↔ | Length | 23 5/8" (600 mm) | 15 3/4" (400 mm) | 27 9/16" (700 mm) | 20 5/64" (510 mm) | 25 63/64" (660 mm) |

003 TECHNICAL PERFORMANCE


| | | |
|---|-----------------------------|--|
|  | Norm | En 14342 |
|  | FSC | CU-COC-874752 |
|  | Formaldehyde emission class | Carb2 |
|  | Flammability class | Dfl-s1 |
|  | Underfloor heating | Yes - Warranty certificate available  |
|  | Floor cooling | Yes - Warranty certificate available  |
|  | Thermal conductivity | 0.17 W/mK |
|  | Moisture content | 7 % (+/- 2%) |
|  | Advisory use | Suitable for: residential, commercial, Hospitality, Retail |

004 ADDITIONAL INFORMATION


| | | |
|---|--------------|------------------------|
|  | Installation | Glued down |
|  | Jointing | Tongue and groove |
|  | Sanding | Yes (1 mm per sanding) |




PRIME
Knots: limited
Cracks: none
Sapwood: none




NATURAL A
Knots: very few
Cracks: none
Sapwood: none




NATURAL AB
Knots: unlimited/filled
Cracks: permitted
Sapwood: none



NATURAL B
Knots: unlimited/filled
Cracks: permitted
Sapwood: none



ART
 Natural rustic look with
 open/half filled knots & cracks
Top layer: planed
Knots: open and/or semi-filled



ART+
 Natural rustic look with
 open/half filled knots & cracks
Top layer: undulating/shrunk knots
Knots: open and/or semi-filled

