







TECHNICAL DATA SHEET - OAK COLLECTION

**OAK FOUR**




**BQO 402 WARM NUDE**



001 PRODUCT DESCRIPTION

	Wood type	European Oak
	Grading	Stormwood
	Core/backing	Plywood
	Coating	Reactive stains & pigmented oil
	Texture	Wheathered look & bandsawn effect
	Bevel	Aged

002 DIMENSIONS

	<b>Straight</b>	<b>Herringbone</b>
 Thickness/surface	19/32"- 5/32" (15/4 mm)	9/64" (15/4 mm)
 Width	7 31/64" (190 mm)	5 33/64" (140 mm)
 Length	74 51/64" (1900 mm)	25 63/64" (700 mm)

## 003 TECHNICAL PERFORMANCE

---

	Norm	En 14342
	FSC	CU-COC-874752
	Formaldehyde emission class	Carb2
	Flammability class	Dfl-s1
	Underfloor heating	Yes - Warranty certificate available 
	Floor cooling	Yes - Warranty certificate available 
	Thermal conductivity	0.17 W/mK
	Moisture content	7 % (+/- 2%)
	Advisory use	Suitable for: residential, commercial, Hospitality, Retail

## 004 ADDITIONAL INFORMATION

---

	Installation	Glued down
	Jointing	Tongue and groove
	Sanding	Yes (1 mm per sanding)



**STORMWOOD**

**Knots :** open, filled manually

**Cracks :** permitted

**Sapwood :** limited

